

# Jeffrey Energy Center FGD Landfill 1A/1B & 1C Run-On and Run-Off Control System Plan

Jeffrey Energy Center  
25905 Jeffrey Rd.  
St. Marys, Kansas

Prepared for:



Energys Kansas Central, Inc.

**SCS ENGINEERS**

25221144.00 | October 2022

40 Shuman Blvd, Ste 216  
Naperville, IL 60563

## Table of Contents

Section	Page
<b>Plan Review/Amendment Log</b> .....	<b>ii</b>
<b>Professional Engineer Certification</b> .....	<b>iii</b>
<b>1.0 Introduction</b> .....	<b>1</b>
<b>2.0 Regulatory Requirements</b> .....	<b>1</b>
<b>3.0 2022 Run-On and Run-Off Control System Plan Update</b> .....	<b>2</b>
3.1 Run-On Control System .....	2
3.2 Run-Off Control System.....	2
3.3 Hydrologic and Hydraulic Analysis.....	3
3.3.1 Rainfall Data .....	3
3.3.2 Model Input Parameters .....	3
3.3.3 Conveyance Features.....	4
3.4 Results and Conclusions.....	4
<b>4.0 Certifications</b> .....	<b>5</b>
<b>5.0 References</b> .....	<b>6</b>

## Figures

- Figure 1. FGD Landfill 1A/1B and 1C Run-On and Run-Off Control System  
Figure 2. Regional Control System – Tower Hill Lake

## Appendices

- Appendix A Rainfall Intensity Table for Kansas Counties  
Appendix B FGD Landfill 1A/1B and 1C Run-Off Control System – HydroCAD Model  
Appendix C Regional Control System Tower Hill Lake – HydroCAD Model



## PROFESSIONAL ENGINEER CERTIFICATION

I, Richard D. Southorn, hereby certify that this Run-On and Run-Off Control System Plan meets the requirements of 40 CFR §257.81, was prepared by me or under my direct supervision, and that I am a duly licensed Professional Engineer under the laws of the State of Kansas.

This plan has been prepared as an update to the initial Run-On and Run-Off Control System Plan that was certified on October 17, 2016 and subsequently updated and certified October 8, 2021.



Richard D. Southorn, PE

License No. PE 25201

Expires 4/30/2023

## 1.0 INTRODUCTION

The FGD Landfill (Landfill) is an existing coal combustion residual (CCR) landfill located at Evergy's Jeffrey Energy Center (JEC) near St. Marys, Kansas. This Run-on and Run-off Control System Plan (RORO Plan) documents that the Landfill's run-on and run-off control systems for the active portions of the landfill (currently Phases 1A, 1B and 1C) meet the applicable requirements of Title 40 Code of Federal Regulations (CFR) §257.81<sup>1</sup> of the CCR Rule.

## 2.0 REGULATORY REQUIREMENTS

### 40 CFR §257.81 Run-on and run-off controls for CCR landfills.

- (a) The owner or operator of an existing or new CCR landfill or any lateral expansion of a CCR landfill must design, construct, operate, and maintain:
  - (1) A run-on control system to prevent flow onto the active portion of the CCR unit during the peak discharge from a 24-hour, 25-year storm; and
  - (2) A run-off control system from the active portion of the CCR unit to collect and control at least the water volume resulting from a 24-hour, 25-year storm.
- (b) Run-off from the active portion of the CCR unit must be handled in accordance with the surface water requirements under 40 CFR §257.3-3<sup>1</sup>.
- (c) Run-on and run-off control system plan
  - (1) Content of the plan. The owner or operator must prepare initial and periodic run-on and run-off control system plans for the CCR unit according to the timeframes specified in paragraphs (c)(3) and (4) of this section. These plans must document how the run-on and run-off control systems have been designed and constructed to meet the applicable requirements of this section. Each plan must be supported by appropriate engineering calculations. The owner or operator has completed the initial run-on and run-off control system plan when the plan has been placed in the facility's operating record as required by 40 CFR §257.105(g)(3).

With reference to 40 CFR §257.81(c) above, the Initial RORO Plan was required to be developed no later than October 17, 2016 for existing landfills (40 CFR §257.81(c)(3)(i))<sup>1</sup>. Updates to the RORO Plan are required whenever there is a change in conditions that would substantially affect the written plan in effect (40 CFR §257.81(2))<sup>1</sup>, or within five years of the previous plan (40 CFR §257.81(c)(4))<sup>1</sup>.

The owner or operator must obtain a certification from a qualified professional engineer or approval from the Participating State Director or approval from EPA where EPA is the permitting authority stating that the initial and periodic RORO Plans meet the requirements of 40 CFR §257.81<sup>1</sup>.

### **3.0 2022 RUN-ON AND RUN-OFF CONTROL SYSTEM PLAN UPDATE**

This document has been prepared as an update to the 2021 RORO Plan to incorporate Phase 1C, which will become operational in 2022. This plan has been developed to reflect run-on and run-off controls that will be used for active areas of the landfill, including Phases 1A, 1B, and 1C. As such, this plan replaces the previous RORO Plan. The current run-on and run-off control systems at the Landfill have been reviewed as part of this 2022 update and have been found to meet the requirements of 40 CFR §257.81(a)<sup>1</sup>, as outlined in Section 2.0.

Conveyance features that comprise the run-on and run-off control systems at the Landfill are depicted in **Figure 1**. Storm water calculations supporting the below discussion are included in **Appendices A through C**.

#### **3.1 RUN-ON CONTROL SYSTEM**

The active portion of the Landfill is surrounded by a containment berm that is designed to prevent contact water run-off. This containment berm is approximately four feet higher than the surrounding exterior grades at its lowest point. The surrounding grades outside of this berm all slope away from the active area of the Landfill. Inactive areas with final cover outside of the containment berm are not included in this evaluation.

#### **3.2 RUN-OFF CONTROL SYSTEM**

As mentioned in Section 3.1, a containment berm has been constructed around the entire active disposal area. Phase 1A/1B and Phase 1C are separated by an approximately 15-foot tall berm. The active portion of Phase 1A/1B ranges between four feet (in the south) and twenty feet (in the north) below the containment berm. The active portion of Phase 1C ranges between four feet (in the south) and forty feet (in the north) below the containment berm. The active areas are graded to flow to the north. Direct precipitation falling on the active portion of the Landfill (contact water) is fully contained within the berm.

Within Phase 1A/1B, contact water flows over the surface of the active area and temporarily collects in the north. It is then conveyed through a pipe and discharges into a downchute lined with riprap. The downchute is also used to control and convey non-contact water that falls on the Phase 1B and 1C final cover system. The downchute discharges into the South Bypass Ditch, which ultimately drains to Tower Hill Lake. The run-off control system is depicted in **Figure1**.

In Phase 1C, contact water flows north over the active area and accumulates at the low spot along the toe of the containment berm. From there, contact water will gradually infiltrate through the protective cover layer and leachate collection system, where it will be conveyed to the Contact Water Basin. The Contact Water Basin ultimately drains to Tower Hill Lake. The run-off control system is depicted in **Figure1**.

Tower Hill Lake is located immediately to the northwest of the Landfill and is permitted to receive non-contact water, contact water, and leachate from the JEC, including multiple landfills and surface impoundments under the facility's National Pollutant Discharge Elimination System (NPDES) Permit. In accordance with 40 CFR §257.81(b)<sup>1</sup>, this is consistent with the surface water requirements under 40 CFR §257.3-3<sup>1</sup>.

## 3.3 HYDROLOGIC AND HYDRAULIC ANALYSIS

Engineering calculations to evaluate the run-off control system at the Landfill consist of a hydrologic and hydraulic storm water model prepared using HydroCAD storm water modeling software. Run-on analyses are not applicable because all surrounding areas slope away from the active area of the Landfill. The run-off control system model for the Landfill is provided in **Appendix B**. A regional model evaluating the capacity within Tower Hill Lake is provided in **Appendix C**. Information used to prepare the HydroCAD storm water model is summarized below.

### 3.3.1 Rainfall Data

Rainfall amounts for the 25-year, 24-hour storm were obtained from the Rainfall Intensity Tables for Counties in Kansas (2014) prepared by Kansas Department of Transportation. This document provides rainfall intensities for various durations and recurrence intervals, displayed in rainfall intensity tables for each county in Kansas. The rainfall intensity table applicable to the Landfill is the table prepared for Pottawatomie County (**Appendix A**). The 25-year, 24-hour rainfall amount for the Landfill was determined to be 6.00-inches, based on a rainfall rate of 0.25 inches/hour for 24 hours.

The Natural Resources Conservation Service (NRCS), formerly the Soil Conservation Service (SCS), Technical Release 55 (TR-55) was consulted to determine the appropriate storm water distribution pattern to model the rainfall depth in HydroCAD. According to TR-55<sup>2</sup>, the Type-II 24-hour storm distribution is appropriate for all counties located in Kansas.

### 3.3.2 Model Input Parameters

Subcatchment areas (also known as watersheds) were delineated using AutoCAD Civil3D 2020 (AutoCAD) based on topographic divides within the analyzed area. Run-off from each subcatchment area was calculated using the NRCS-SCS Technical Release 20 (TR-20) method that utilizes curve numbers and flow length parameters to calculate storm water run-off. These areas are depicted in **Figure 1**.

For the regional Tower Hill Lake model, the subcatchment area was delineated using the United States Geological Survey (USGS) 7.5-minute topographic quadrangle map. This subcatchment area is depicted in **Figure 2**.

The Curve number (CN) is a parameter used to determine the amount of runoff that will occur from a surface. High CN values indicate that the majority of rainfall will run off with minimal losses. Lower values correspond to an increased ability of rainfall to infiltrate the ground surface, leading to lower run off rates.

A curve number of 92 was selected for all areas with surficial FGD material, based on a review of the Hydrologic Evaluation of Landfill Performance (HELP) model completed as part of the 2009 Solid Waste Permit Application.

For Landfill covers associated with the regional Tower Hill Lake model, the soil type and ground cover were considered to select the appropriate curve number using NRCS lookup tables. According to the NRCS Web Soil Survey for Pottawatomie County<sup>3</sup>, the predominant soil type within the JEC footprint is Hydrologic Soil Group D (HSG-D). HSG-D soils provide the highest curve numbers of all soil types. Therefore, all subcatchment areas have been modeled with this soil type designation.

The land cover applicable for the regional Tower Hill Lake model consists of open space with good grass cover (CN=80) and water surface (CN=98).

The time of concentration, defined as the longest amount of time a waterdrop would take to travel from the headwater of a subcatchment area to its downstream edge, was delineated in AutoCAD and entered for the subcatchment in HydroCAD.

### 3.3.3 Conveyance Features

Direct precipitation falling on the active portion of the Landfill collects within the containment berm system and discharges to Tower Hill Lake through a pipe, rip-rap lined downchute, and the South Bypass Ditch. Key attributes used in the Landfill run-off HydroCAD model for each conveyance feature are summarized below:

- Perimeter Berm System and Active Disposal Area (HydroCAD Nodes - P1AB and P1C)
  - Modeled with incremental detention volume using minor and major contour intervals
- Discharge Pipe (HydroCAD Node - P1AB)
  - 24-in. diameter, high-density polyethylene (HDPE) pipe from Perimeter Berm System to the Permanent Downchute.
- Permanent Downchute (HydroCAD Node - D1AB)
  - 2-ft. deep channel, 10-ft. wide bottom, with 3H:1V sideslopes.
  - Ditch lining designated as 1-ft. diameter riprap.
- South Bypass Ditch (HydroCAD Node - SBD)
  - Modeled as “Link” that directly connects the flow from the Permanent Ditch to Tower Hill Lake.
- Terrace Bench (HydroCAD Nodes – TB1, TB2, TB3)
  - Terrace benches are designed to drain the final cover slopes of the landfill and convey runoff to the Permanent Downchute where it eventually reaches the South Bypass Ditch.
  - 1-ft deep, v-notch bench with 4H:1V interior slope and 20H:1V outer slope. The benches drain to the permanent downchute with slopes between 2-3%.

These conveyance paths are modeled in HydroCAD to demonstrate the run-on/run-off control system is appropriately sized to accommodate the 25-year, 24-hour storm event.

Tower Hill Lake is designed to serve as the run-off control pond for the Landfill and other portions of the JEC. Tower Hill Lake was modeled with incremental detention volume defined by contour intervals between the normal water elevation (approximate elevation 1,146.0 ft. MSL) to the lowest elevation of the perimeter berm (approximate elevation 1,166.0 ft. MSL). Tower Hill Lake is modeled to demonstrate the run-off control system is appropriately sized to accommodate total discharge rate from the Landfill for the 25-year, 24-hour storm event.

## 3.4 RESULTS AND CONCLUSIONS

The surrounding grades proximate to Phases 1A/1B and 1C all slope away from the active area of the landfill. Therefore, there is no potential for storm water run-on to enter the active area of the landfill. As such, the landfill meets the requirements of 40 CFR §257.81(a)(1)<sup>1</sup>.

The HydroCAD storm water model of the Landfill was developed to evaluate whether the peak flow run-off from the 25-year, 24-hour storm event could be accommodated without overtopping the run-off control systems.

The Landfill run-off control system is designed and constructed to divert contact water in a controlled manner to Tower Hill Lake. Based on the results of the HydroCAD storm water model, the run-off control system was determined to accommodate the 25-year, 24-hour storm event without overtopping and meets the requirements of 40 CFR §257.81(a)(2)<sup>1</sup>. The peak depth and freeboard remaining within each conveyance feature is summarized below:

<b>Table 1 – Conveyance Feature Sizing</b>		
<b>Conveyance Feature Designation</b>	<b>Peak Depth (feet)</b>	<b>Freeboard (feet)</b>
Phase 1A/1B		
Perimeter Berm System	1.65 (north area)	18.35 (relative to high water level location)
Permanent Downchute	0.49'	1.51'
Phase 1C		
Perimeter Berm System	13.7 (north area)	14.3 (relative to high point in active area - 1222' MSL)

Based on the results from the regional HydroCAD model, Tower Hill Lake is designed to collect and control the water volume resulting from the 25-year, 24-hour storm event for the Landfill and other portions of the JEC without overtopping. The peak depth and freeboard remaining within Tower Hill Lake is summarized below:

<b>Table 2 – Tower Hill Lake Capacity</b>		
<b>Peak Rise in Water Elevation (feet)</b>	<b>Available Freeboard (feet)</b>	<b>Remaining Capacity (acre-feet)</b>
2.70	17.30	2,804.6

## 4.0 CERTIFICATIONS


Richard D. Southorn, a licensed Professional Engineer in the State of Kansas, has overseen the preparation of this Run-On and Run-Off Control System Plan. A certification statement in accordance with 40 CFR §257.81(c)(5)<sup>1</sup> is provided on **Page iii** of this plan.

## 5.0 REFERENCES

1. U.S. Environmental Protection Agency, Standards for the Disposal of Coal Combustion Residuals in Landfills and Surface Impoundments, Title 40 Code of Federal Regulations Part §257. Federal Register 80, Subpart D, dated April 17, 2015.
2. USDA Natural Resources Conservation Service, Technical Release 55, dated June 1986.
3. USDA Natural Resources Conservation Service, Web Soil Survey for Pottawatomie County <https://websoilsurvey.sc.egov.usda.gov/App/HomePage.htm>, dated 2021.

## Figures

- Figure 1. FGD Landfill 1A/1B and 1C Run-On and Run-Off Control System
- Figure 2. Regional Control System – Tower Hill Lake



**LEGEND**

- SUBCATCHMENT BOUNDARY
- APPROXIMATE PHASE BOUNDARY
- SOUTH BYPASS DITCH
- WATER CONVEYANCE FEATURE LOCATION
- - - - - TIME OF CONCENTRATION FLOW PATH
- CONTAINMENT BERM
- FINAL COVER
- SC1AB-1 SUBCATCHMENT NUMBER

**NOTES**

1. EXISTING SITE TOPOGRAPHY DEVELOPED BY PROFESSIONAL ENGINEERING CONSULTANTS (PEC) IN DECEMBER 2020



SCALE: 1" = 250'

PROJECT NO.	25221144	DRAWN BY:	NV
DRAWN:	08/24/2022	CHECKED BY:	RDS
REVISED:	-	APPROVED BY:	

**ENGINEER**

**SCS ENGINEERS**

40 SHUMAN BLVD, STE 216, NAPERVILLE, IL 60563  
PHONE: (331) 806-4300

**CLIENT**


**SITE**

JEFFREY ENERGY CENTER  
ST. MARYS, KS

RUN-ON AND RUN-OFF PLAN  
SUBCATCHMENT AREA

FIGURE  
1 OF 2

I:\25221144.00\Drawings\Ph1\C\Figures\RO\Site Layout-HydroCAD.dwg, 10/7/2022 11:01:43 AM




LEGEND

- CCR UNIT BOUNDARY
- WATERSHED BOUNDARY
- ←← TIME OF CONCENTRATION

NOTES:

1. FIGURE ADAPTED FROM USGS 7.5-MINUTE TOPOGRAPHIC QUADRANGLE FROM EMMETT AND LECLEDE, KS (2018).
2. ALL BOUNDARIES ARE APPROXIMATE.



PROJECT NO. 25221157  
 DRAWN: 08/26/2021  
 REVISED:

DRAWN BY: SJL  
 CHECKED BY: RDS  
 APPROVED BY:

**SCS ENGINEERS**  
 2830 DAIRY DRIVE MADISON, WI 53718-6751  
 PHONE: (608) 224-2830

**evergy**

SITE: JEFFREY ENERGY CENTER  
 ST. MARYS, KS

JEFFREY ENERGY CENTER  
 REGIONAL CONTROL SYSTEM  
 TOWER HILL LAKE

FIGURE  
 2 OF 2

## Appendices

- Appendix A      Rainfall Intensity Table for Kansas Counties
- Appendix B      FGD Landfill 1A/1B and 1C Run-On and Run-Off  
Control System – HydroCAD Output Files
- Appendix C      Regional Control System Tower Hill Lake – HydroCAD  
Output Files

## Appendix A      Rainfall Intensity Table for Kansas Counties

# MEMO



## ROAD MEMORANDUM NO. 16-03

DATE: September 2, 2016

SUBJECT: *Rainfall Intensity Tables*

The publication, *Rainfall Intensity Tables for Counties in Kansas*, dated June 1997, has recently be updated and replaced by *Rainfall Intensity Tables for Counties in Kansas (2014)*.

The new tables were developed from the National Oceanic and Atmospheric Administration (NOAA) Atlas 14 Volume 8 (Perica et al. 2013) which was recently released by the National Weather Service (NWS) Hydro Meteorological Design Studies Center. The new tables provide rainfall intensities for durations from 5 minutes to 24 hours and various recurrence intervals from 1-500 years.

The *Rainfall Intensity Tables for Counties in Kansas (2014)* supersede the previous rainfall tables based on TP-40 and HYDRO-35 (McEnroe 1997). The new rainfall tables are available on the Kansas Department of Transportation's (KDOT) website at <http://kart.ksdot.org>.

If you have any questions, please contact John Hobelman at (785) 368-8791.

A handwritten signature in blue ink that reads "Scott W. King".

Scott W. King, P.E., Chief  
Bureau of Road Design

SWK:js

By e-mail: American Council of Engineering Companies  
Federal Highway Administration  
Kansas Contractors Association ([kca@ink.org](mailto:kca@ink.org))  
Active Consultants  
Director of Engineering & Design  
Director of Operations  
District Engineers  
Area Engineers  
Chief, Bureau of Local Projects  
Chief, Bureau of Right of Way  
Chief, Bureau of Transportation Safety & Technology  
Chief, Bureau of Construction & Materials  
Chief, Bureau of Maintenance  
Chief, Bureau of Structures and Geotechnical Services  
Road Design/Squad Leaders  
Coordinating Section

**Rainfall Intensity  
Tables  
for  
Counties in Kansas**



**(December, 2014 Edition)**



## RAINFALL INTENSITY TABLE

## POTTAWATOMIE COUNTY, KANSAS

This table contains average rainfall intensities in inches per hour.

DURATION (H:M)	AVERAGE RECURRENCE INTERVAL								
	1 yr	2 yr	5 yr	10 yr	25 yr	50 yr	100 yr	200 yr	500 yr
3:15	0.58	0.68	0.87	1.03	1.27	1.47	1.68	1.91	2.22
3:30	0.55	0.65	0.82	0.98	1.21	1.40	1.59	1.81	2.11
3:45	0.52	0.61	0.78	0.93	1.15	1.33	1.52	1.72	2.00
4:00	0.49	0.58	0.74	0.88	1.09	1.26	1.44	1.64	1.91
4:15	0.47	0.56	0.71	0.84	1.04	1.21	1.38	1.56	1.82
4:30	0.45	0.53	0.68	0.81	1.00	1.16	1.32	1.50	1.74
4:45	0.43	0.51	0.65	0.78	0.96	1.11	1.27	1.44	1.67
5:00	0.42	0.49	0.63	0.74	0.92	1.06	1.22	1.38	1.61
5:15	0.40	0.47	0.60	0.72	0.89	1.02	1.17	1.33	1.54
5:30	0.39	0.46	0.58	0.69	0.85	0.99	1.13	1.28	1.49
5:45	0.37	0.44	0.56	0.67	0.82	0.95	1.09	1.23	1.43
6:00	0.36	0.43	0.54	0.64	0.80	0.92	1.05	1.19	1.38
6:30	0.34	0.40	0.51	0.61	0.75	0.86	0.99	1.12	1.30
7:00	0.32	0.38	0.48	0.57	0.70	0.81	0.93	1.05	1.22
7:30	0.30	0.36	0.46	0.54	0.67	0.77	0.88	0.99	1.15
8:00	0.29	0.34	0.43	0.51	0.63	0.73	0.83	0.94	1.09
8:30	0.27	0.32	0.41	0.49	0.60	0.70	0.79	0.90	1.04
9:00	0.26	0.31	0.39	0.47	0.57	0.66	0.76	0.85	0.99
9:30	0.25	0.30	0.38	0.45	0.55	0.63	0.72	0.81	0.94
10:00	0.24	0.28	0.36	0.43	0.53	0.61	0.69	0.78	0.90
10:30	0.23	0.27	0.35	0.41	0.50	0.58	0.66	0.75	0.86
11:00	0.22	0.26	0.33	0.40	0.49	0.56	0.64	0.72	0.83
11:30	0.21	0.25	0.32	0.38	0.47	0.54	0.61	0.69	0.80
12:00	0.21	0.24	0.31	0.37	0.45	0.52	0.59	0.66	0.77
13:00	0.19	0.23	0.29	0.34	0.42	0.48	0.55	0.62	0.72
14:00	0.18	0.22	0.27	0.32	0.39	0.45	0.51	0.58	0.67
15:00	0.17	0.20	0.26	0.30	0.37	0.43	0.48	0.55	0.63
16:00	0.16	0.19	0.24	0.29	0.35	0.40	0.46	0.52	0.59
17:00	0.16	0.18	0.23	0.27	0.33	0.38	0.43	0.49	0.56
18:00	0.15	0.18	0.22	0.26	0.32	0.36	0.41	0.46	0.53
19:00	0.14	0.17	0.21	0.25	0.30	0.35	0.39	0.44	0.51
20:00	0.14	0.16	0.20	0.24	0.29	0.33	0.37	0.42	0.49
21:00	0.13	0.15	0.19	0.23	0.28	0.32	0.36	0.40	0.46
22:00	0.13	0.15	0.19	0.22	0.27	0.30	0.34	0.39	0.45
23:00	0.12	0.14	0.18	0.21	0.26	0.29	0.33	0.37	0.43
24:00	0.12	0.14	0.17	0.20	0.25	0.28	0.32	0.36	0.41

Appendix B      FGD Landfill 1A/1B and 1C Run-On and Run-Off  
Control System – HydroCAD Output Files



**FGD Landfill**

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 2

**Summary for Subcatchment 1AB-1: 1AB-1**

Runoff = 83.11 cfs @ 12.23 hrs, Volume= 8.401 af, Depth= 5.07"

Routed to Pond P1AB : Perimeter Berm System + Discharge Pipe

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Type II 24-hr 25-year, 24-hour Rainfall=6.00"


Area (ac)	CN	Description
* 19.886	92	CCR Material, HSG-D
19.886		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.1	100	0.0367	0.54		<b>Sheet Flow,</b> Fallow n= 0.050 P2= 3.36"
27.0	1,449	0.0080	0.89		<b>Shallow Concentrated Flow,</b> Nearly Bare & Untilled Kv= 10.0 fps
30.1	1,549	Total			

**Subcatchment 1AB-1: 1AB-1**

Hydrograph



**FGD Landfill**

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 3

**Summary for Subcatchment 1AB-2: 1AB-2**

Runoff = 2.56 cfs @ 11.92 hrs, Volume= 0.113 af, Depth= 3.18"  
 Routed to Reach TB2 : TB2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Area (sf)	CN	Description
18,510	74	>75% Grass cover, Good, HSG C
18,510		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
2.0	50	0.2500	0.42		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.36"

**Subcatchment 1AB-2: 1AB-2**

Hydrograph



**FGD Landfill**

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 4

**Summary for Subcatchment 1AB-3: 1AB-3**

Runoff = 10.57 cfs @ 11.94 hrs, Volume= 0.465 af, Depth= 3.18"  
 Routed to Reach TB3 : TB3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Type II 24-hr 25-year, 24-hour Rainfall=6.00"


Area (sf)	CN	Description
76,293	74	>75% Grass cover, Good, HSG C
76,293		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.5	100	0.2500	0.48		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.36"
0.1	17	0.2500	3.50		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
3.6	117	Total			

**Subcatchment 1AB-3: 1AB-3**

Hydrograph



**FGD Landfill**

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 5

**Summary for Subcatchment 1C-1: 1C-1**

Runoff = 62.25 cfs @ 11.97 hrs, Volume= 3.406 af, Depth= 5.07"  
 Routed to Pond P1C : Perimeter Berm System

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Type II 24-hr 25-year, 24-hour Rainfall=6.00"


Area (ac)	CN	Description
* 8.063	92	CCR Material
8.063		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
2.6	100	0.0600	0.65		<b>Sheet Flow,</b> Fallow n= 0.050 P2= 3.36"
4.1	620	0.0650	2.55		<b>Shallow Concentrated Flow,</b> Nearly Bare & Untilled Kv= 10.0 fps
6.7	720	Total			

**Subcatchment 1C-1: 1C-1**

Hydrograph



**FGD Landfill**

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 6

**Summary for Subcatchment 1C-2: 1C-2**

Runoff = 12.12 cfs @ 11.94 hrs, Volume= 0.535 af, Depth= 3.18"  
 Routed to Reach TB1 : TB1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Type II 24-hr 25-year, 24-hour Rainfall=6.00"


Area (sf)	CN	Description
87,748	74	>75% Grass cover, Good, HSG C
87,748		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.5	100	0.2500	0.48		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.36"
0.2	50	0.2500	3.50		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
3.7	150	Total			

**Subcatchment 1C-2: 1C-2**

Hydrograph



# FGD Landfill

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 7

## Summary for Reach D1AB: Permanent Downchute

Inflow Area = 24.077 ac, 0.00% Impervious, Inflow Depth > 4.65" for 25-year, 24-hour event  
Inflow = 25.26 cfs @ 12.01 hrs, Volume= 9.324 af  
Outflow = 24.27 cfs @ 12.04 hrs, Volume= 9.322 af, Atten= 4%, Lag= 1.9 min  
Routed to Link SBD : South Bypass Ditch

Routing by Stor-Ind+Trans method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs

Max. Velocity= 4.45 fps, Min. Travel Time= 1.1 min

Avg. Velocity = 1.55 fps, Avg. Travel Time= 3.2 min

Peak Storage= 1,670 cf @ 12.03 hrs

Average Depth at Peak Storage= 0.49' , Surface Width= 12.92'

Bank-Full Depth= 2.00' Flow Area= 32.0 sf, Capacity= 319.58 cfs

10.00' x 2.00' deep channel, n= 0.078 Riprap, 12-inch

Side Slope Z-value= 3.0 ' / ' Top Width= 22.00'


Length= 300.0' Slope= 0.1733 ' / '

Inlet Invert= 1,224.00', Outlet Invert= 1,172.00'



## Reach D1AB: Permanent Downchute

### Hydrograph



# FGD Landfill

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 8


## Summary for Reach TB1: TB1

Inflow Area = 2.014 ac, 0.00% Impervious, Inflow Depth = 3.18" for 25-year, 24-hour event  
Inflow = 12.12 cfs @ 11.94 hrs, Volume= 0.535 af  
Outflow = 10.69 cfs @ 12.02 hrs, Volume= 0.535 af, Atten= 12%, Lag= 4.7 min  
Routed to Reach D1AB : Permanent Downchute

Routing by Stor-Ind+Trans method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
Max. Velocity= 3.40 fps, Min. Travel Time= 2.9 min  
Avg. Velocity = 1.13 fps, Avg. Travel Time= 8.6 min


Peak Storage= 1,833 cf @ 11.97 hrs  
Average Depth at Peak Storage= 0.51' , Surface Width= 12.29'  
Bank-Full Depth= 1.00' Flow Area= 12.0 sf, Capacity= 64.20 cfs

0.00' x 1.00' deep channel, n= 0.025 Earth, clean & winding  
Side Slope Z-value= 4.0 20.0 '/' Top Width= 24.00'  
Length= 583.0' Slope= 0.0206 '/'  
Inlet Invert= 1,210.00', Outlet Invert= 1,198.00'



## Reach TB1: TB1

### Hydrograph



# FGD Landfill

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 9


## Summary for Reach TB2: TB2

Inflow Area = 0.425 ac, 0.00% Impervious, Inflow Depth = 3.18" for 25-year, 24-hour event  
Inflow = 2.56 cfs @ 11.92 hrs, Volume= 0.113 af  
Outflow = 2.34 cfs @ 12.00 hrs, Volume= 0.113 af, Atten= 9%, Lag= 4.8 min  
Routed to Reach D1AB : Permanent Downchute

Routing by Stor-Ind+Trans method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
Max. Velocity= 2.65 fps, Min. Travel Time= 3.1 min  
Avg. Velocity = 0.91 fps, Avg. Travel Time= 8.9 min


Peak Storage= 431 cf @ 11.95 hrs  
Average Depth at Peak Storage= 0.27' , Surface Width= 6.52'  
Bank-Full Depth= 1.00' Flow Area= 12.0 sf, Capacity= 75.87 cfs

0.00' x 1.00' deep channel, n= 0.025 Earth, clean & winding  
Side Slope Z-value= 4.0 20.0 '/' Top Width= 24.00'  
Length= 487.0' Slope= 0.0287 '/'  
Inlet Invert= 1,238.00', Outlet Invert= 1,224.00'



## Reach TB2: TB2

### Hydrograph



# FGD Landfill

Prepared by SCS Engineers

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Printed 8/24/2022

Page 10


## Summary for Reach TB3: TB3

Inflow Area = 1.751 ac, 0.00% Impervious, Inflow Depth = 3.18" for 25-year, 24-hour event  
Inflow = 10.57 cfs @ 11.94 hrs, Volume= 0.465 af  
Outflow = 9.40 cfs @ 12.00 hrs, Volume= 0.465 af, Atten= 11%, Lag= 3.5 min  
Routed to Reach D1AB : Permanent Downchute

Routing by Stor-Ind+Trans method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
Max. Velocity= 3.61 fps, Min. Travel Time= 2.1 min  
Avg. Velocity = 1.22 fps, Avg. Travel Time= 6.3 min


Peak Storage= 1,246 cf @ 11.97 hrs  
Average Depth at Peak Storage= 0.47' , Surface Width= 11.33'  
Bank-Full Depth= 1.00' Flow Area= 12.0 sf, Capacity= 71.81 cfs

0.00' x 1.00' deep channel, n= 0.025 Earth, clean & winding  
Side Slope Z-value= 4.0 20.0 '/' Top Width= 24.00'  
Length= 466.0' Slope= 0.0258 '/'  
Inlet Invert= 1,208.00', Outlet Invert= 1,196.00'



## Reach TB3: TB3

### Hydrograph



**FGD Landfill**

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Prepared by SCS Engineers

Printed 8/24/2022

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Page 11

**Summary for Pond P1AB: Perimeter Berm System + Discharge Pipe**

Inflow Area = 19.886 ac, 0.00% Impervious, Inflow Depth = 5.07" for 25-year, 24-hour event  
 Inflow = 83.11 cfs @ 12.23 hrs, Volume= 8.401 af  
 Outflow = 9.52 cfs @ 13.25 hrs, Volume= 8.211 af, Atten= 89%, Lag= 61.3 min  
 Primary = 9.52 cfs @ 13.25 hrs, Volume= 8.211 af  
 Routed to Reach D1AB : Permanent Downchute

Routing by Stor-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Peak Elev= 1,223.65' @ 13.25 hrs Surf.Area= 4.876 ac Storage= 4.898 af

Plug-Flow detention time= 379.1 min calculated for 8.211 af (98% of inflow)  
 Center-of-Mass det. time= 364.8 min ( 1,160.9 - 796.1 )

Volume	Invert	Avail.Storage	Storage Description
#1	1,222.00'	268.652 af	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)


Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)
1,222.00	1.077	0.000	0.000
1,224.00	5.695	6.772	6.772
1,226.00	8.592	14.287	21.059
1,228.00	10.822	19.414	40.473
1,230.00	12.859	23.681	64.154
1,232.00	15.858	28.717	92.871
1,234.00	16.828	32.686	125.557
1,236.00	17.373	34.201	159.758
1,238.00	17.898	35.271	195.029
1,240.00	18.403	36.301	231.330
1,242.00	18.919	37.322	268.652

Device	Routing	Invert	Outlet Devices
#1	Primary	1,222.00'	<b>24.0" Round Temp Contact Water Pipe</b> L= 440.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 1,222.00' / 1,200.00' S= 0.0500 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

**Primary OutFlow** Max=9.53 cfs @ 13.25 hrs HW=1,223.65' (Free Discharge)  
 ↑1=Temp Contact Water Pipe (Inlet Controls 9.53 cfs @ 3.45 fps)

**Pond P1AB: Perimeter Berm System + Discharge Pipe**

Hydrograph



**FGD Landfill**

Type II 24-hr 25-year, 24-hour Rainfall=6.00"

Prepared by SCS Engineers

Printed 8/24/2022

HydroCAD® 10.20-2d s/n 05804 © 2021 HydroCAD Software Solutions LLC

Page 13

**Summary for Pond P1C: Perimeter Berm System**

Inflow Area = 8.063 ac, 0.00% Impervious, Inflow Depth = 5.07" for 25-year, 24-hour event  
 Inflow = 62.25 cfs @ 11.97 hrs, Volume= 3.406 af  
 Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min


Routing by Stor-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Peak Elev= 1,207.71' @ 24.40 hrs Surf.Area= 34,975 sf Storage= 148,371 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)  
 Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	1,194.00'	1,376,254 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
1,194.00	98	0	0
1,196.00	644	742	742
1,198.00	1,803	2,447	3,189
1,200.00	4,367	6,170	9,359
1,202.00	10,293	14,660	24,019
1,204.00	17,804	28,097	52,116
1,206.00	26,132	43,936	96,052
1,208.00	36,461	62,593	158,645
1,210.00	48,572	85,033	243,678
1,212.00	61,471	110,043	353,721
1,214.00	76,408	137,879	491,600
1,216.00	92,836	169,244	660,844
1,218.00	109,656	202,492	863,336
1,220.00	127,853	237,509	1,100,845
1,222.00	147,556	275,409	1,376,254

Pond P1C: Perimeter Berm System

Hydrograph




### Summary for Link SBD: South Bypass Ditch

Inflow Area = 24.077 ac, 0.00% Impervious, Inflow Depth > 4.65" for 25-year, 24-hour event  
Inflow = 24.27 cfs @ 12.04 hrs, Volume= 9.322 af  
Primary = 24.27 cfs @ 12.04 hrs, Volume= 9.322 af, Atten= 0%, Lag= 0.0 min  
Routed to nonexistent node THL


Primary outflow = Inflow, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs

### Link SBD: South Bypass Ditch


Hydrograph





Appendix C      Regional Control System Tower Hill Lake – HydroCAD  
Output Files



Tower Hill Lake




Jeffrey Energy Center  
Watershed



Subcat



Reach



Pond



Link

**Routing Diagram for Tower Hill Lake**

Prepared by SCS Engineers, Printed 9/21/2021

HydroCAD® 10.10-6a s/n 05804 © 2020 HydroCAD Software Solutions LLC

**Tower Hill Lake**

Prepared by SCS Engineers

HydroCAD® 10.10-6a s/n 05804 © 2020 HydroCAD Software Solutions LLC

Type II 24-hr 25-year,24-hour Rainfall=6.00"

Printed 9/21/2021

Page 1

**Summary for Subcatchment JEC: Jeffrey Energy Center Watershed**

Runoff = 373.09 cfs @ 19.35 hrs, Volume= 327.067 af, Depth> 3.88"  
 Routed to Pond THL : Tower Hill Lake


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
 Type II 24-hr 25-year,24-hour Rainfall=6.00"

Area (ac)	CN	Description
934.496	80	>75% Grass cover, Good, HSG D
76.352	98	Water Surface, 0% imp, HSG D
1,010.848	81	Weighted Average
1,010.848		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.2	100	0.0400	0.23		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.36"
13.5	1,138	0.0400	1.40		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
541.4	7,573	0.1000	0.23	6.99	<b>Channel Flow,</b> Area= 30.0 sf Perim= 4,737.0' r= 0.01' n= 0.069 Riprap, 6-inch
562.1	8,811	Total			

**Subcatchment JEC: Jeffrey Energy Center Watershed**

Hydrograph



# Tower Hill Lake

Prepared by SCS Engineers

HydroCAD® 10.10-6a s/n 05804 © 2020 HydroCAD Software Solutions LLC

Type II 24-hr 25-year,24-hour Rainfall=6.00"

Printed 9/21/2021

Page 2

## Summary for Pond THL: Tower Hill Lake

Inflow Area = 1,010.848 ac, 0.00% Impervious, Inflow Depth > 3.88" for 25-year,24-hour event  
Inflow = 373.09 cfs @ 19.35 hrs, Volume= 327.067 af  
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.05 hrs  
Peak Elev= 1,148.70' @ 48.00 hrs Surf.Area= 124.166 ac Storage= 327.058 af

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)  
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	1,146.00'	2,804.565 af	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)
1,146.00	117.180	0.000	0.000
1,148.00	122.922	240.102	240.102
1,150.00	126.458	249.380	489.482
1,152.00	130.703	257.161	746.643
1,154.00	134.795	265.498	1,012.141
1,156.00	138.961	273.756	1,285.897
1,158.00	143.457	282.418	1,568.315
1,160.00	148.544	292.001	1,860.316
1,162.00	154.180	302.724	2,163.040
1,164.00	160.146	314.326	2,477.366
1,166.00	167.053	327.199	2,804.565

# Tower Hill Lake

Prepared by SCS Engineers

HydroCAD® 10.10-6a s/n 05804 © 2020 HydroCAD Software Solutions LLC

Type II 24-hr 25-year,24-hour Rainfall=6.00"

Printed 9/21/2021

Page 3

## Pond THL: Tower Hill Lake

Hydrograph

